

299152



Ergonomische aluminium
steel met waterdoorvoer,
slangpilaar, Ø31 mm, 1560
mm, Zwart



Professionele steel met waterdoorvoer. Met geïsoleerde handgreep en slipvaste grip.

Technical Data

Item Number	299152
Connection	Draad
Materiaal	Geanodiseerd aluminium Polypropyleen Verchroomd messing
Meets the REACH Regulation (EC) No. 1907/2006	Yes **
Complies with California Proposition 65	Nee
SCIP number	e49c50b5-7653-429c-b8f3-803d37b5fetc
Is Halal and Kosher compliant	Ja
PFAS opzettelijk toegevoegd	Nee
Aantal per collo	10 Pcs.
Aantal per pallet (80 x 120 x 180 cm)	400 Pcs.
Quantity Per Layer (Pallet)	40 Pcs.
Collo lengte/Diepte	1610 mm
Collo breedte	160 mm
Collo hoogte	70 mm
Product diameter	31 mm
Product Length/Depth	1560 mm
Breedte	31 mm
Hoogte	31 mm
Netto gewicht	0,58 kg
Gewicht doos (Recycling symbol "20" PAP)	0,03 kg
Total Tare Weight	0,03 kg
Bruto gewicht	0,61 kg
Kubieke meter	0,001499 M3
Maximale druk Bar	6 Bar
Maximale gebruikstemperatuur (voor non food contact)	50 °C
Min. pH-value in usage concentration	4 pH
Maximale pH-waarde in gebruik	11 pH
GTIN-13 code	5705022991019
GTIN-14 code	15705022991016
Commodity code	76169990
Land van oorsprong ISO Code	DK
Land van oorsprong	Denmark

** Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH

Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is registered in the EU SCIP database. Please find SCIP number above.